


Industrial Series

"Workhorse" Laminator HD-25



Most dependable ...productive ... trouble-free ...easy to use ... versatile ...easy to maintain...

These are the kinds of terms owners use to describe their Heavy Duty 25's. There are "Workhorses" 20 years and older that are still going strong. There are owners with several machines that have produced for years with no maintenance other than oiling, adjusting, and replacing "normal wear" parts. In fact, we hear from appreciative owners every month.

They say a HD-25 absorbs tremendous usage with amazing durability, produces high-quality lamination, and easily handles a wider range of jobs than any other 25-inch laminator.

It is an ideal machine for the owners of smaller inkjet printers and other digital imaging devices, because it will mount or mount and laminate in a single pass on boards up to 1/2-inch thick. It will handle different materials without setup changes, run polypropylene film, laminate one-sided, and do cold lamination with the addition of a release liner takeup.

Who can use a Workhorse? Any graphics or finishing shop that needs a true commercial machine... trade laminators, big color imaging shops, photo finishers, printers, government or school support centers, binders & finishers, military installations, hospitals, reprographers, map makers, publishers, and manufacturers.

The HD-25 machine is unique because of its toughness and because no other

manufacturer offers a low cost autofeeder designed specifically for a 25-inch commercial machine. With the addition of our automatic cutter, a rugged and fully automatic laminating system can be assembled for many thousands of dollars less than any other commercial auto-system on the market.

- **Intelligent heat controls** display both the set temperature and the actual temperature. The microprocessor in the control quickly learns to anticipate the heat demand of each job and keeps the actual temperature within a few degrees of the set temperature.
- **Laminating and pull rollers** are covered with quality silicone rubber for superior release quality, higher lamination quality, and easier cleaning. The laminating rollers and pull rollers are interchangeable.
- **Built-in retractable slitters** save an enormous amount of cutting time by trimming away side scrap during the lamination process. The two heads can be adjusted independently with great precision.
- **Dual tension knobs (clutches)** for each supply roll mandrel are easy to use and provide as little or as much tension as needed to keep work wrinkle-free.

- **Forced air cooling** is essential when running thicker films, because the lamination needs to be cooled to get good results.
- **Easy access controls** are conveniently located and grouped for effective operation.
- **Safety guard** is built into the feed tray to help insure it will always be in place when laminating.
- **Both upper and lower rollers** are driven to minimize the wrinkling or curling that can occur when only one roller is driven.
- **Standard precision feed tray** has both left and right side guides and can be replaced with the power feed tray in seconds.
- **Made in the U.S.A.** means quality, better service, and faster parts availability.
- **Two-year manufacturers parts and labor warranty.**



Industrial Series

"Workhorse" Laminator HD-25

OPTIONS

The **power feed tray** is designed exclusively for the Workhorse laminator. This feeder has received good reviews for its effectiveness and easy setup. Automation of feeding is the first step toward automated lines and lower production costs. Additional information is available for this product.

Risers raise machine off work surface, allowing longer supply roll **extensions**, to handle larger diameter rolls of film.

Heavy duty tubular **steel stand** is designed to place unit at optimum feeding height, and to provide a secure base.

Upper fan assembly for running thicker films; additional cooling capacity permits work to be run at a higher speed.

Scrap rewind removes liner material from pressure sensitive and dry resist films.

Footage counter for accurate measurement of film usage.

Additional slitter heads for multiple-up work.

SPECIFICATIONS

Max laminating width	25"
Speed.....	0-25 fpm
Laminating roller diameter	1.5"
Supply roll core size.....	3" (2 1/4" opt)
Recommended film	up to 10 mil
Max laminating thickness.....	1/2"
Max film roll diam	8" (14" opt)
Dimensions.....	36"L x 21"H x 30"D
Shipping Dimensions	57"L x 36"H x 43"W
Weight/Shipping weight	285/500 lbs
Electrical	220V 20 amps 3500 watts
Motor.....	1/4 HP DC

Specifications are subject to change without notice.

You can preserve and protect:

Teaching Aids
ID Cards/Badges
Art Work
Flash Cards
Visuals
Awards
Games
Photographs
Recipes

Presentations
Posters
Charts
Menus
Name Tags
Certificates
Price Lists
Sales Aids
POP Displays

Flyers
Maps
Spec Sheets
Signs
Dry Erase Charts
Bookmarks
Promotional Items
Reports
Public Notices

Luggage Tags
Membership Cards
Place Mats
News Clippings
Safety Warnings
Book Jackets
Licenses
Instructional Material
Memorabilia

Member:

