

Solvent Media

Adhesive Vinyl Technical Data Sheet

PSA Matte White Vinyl Ultra Removable 6 mil

PSA White Ultra Removable Vinyl is used for highly effective advertisements and promotions. With an ultra removable and reusable adhesive it can be applied to smooth and most painted walls. It comes in white matte for digital eco-solvent and solvent printing.

Technical Properties

Caliper/Gauge:	6 mil (13 mil with liner)	Ink: Mild Solvent, Eco-Solvent, Latex
Tensile Strength:	8/10 oz./inch	Opacity: 90%
Adhesive:	water based	Gloss (60°): 10
Availability:	30", 54", 60"	Whiteness:
Printing Environment:		
Ideal Storage Conditions:	Temperature 70°F, 50% Relative Humidity in original packaging.	
Shelf Life:	One year at ideal storage conditions	

Printing Tips:

PSA White Ultra Removable Vinyl is used for highly effective advertisements and promotions. With an ultra removable and reusable adhesive it can be applied to smooth and most painted walls. It comes in white matte for digital eco-solvent and solvent printing.

Finishing/Mounting Recommendations:

Do not apply to unfinished walls.
Only apply after print has cured, and apply to a dry (non-wet) wall.
Not suitable for over laminates
Individual graphic not to exceed 60" & 84"
Panels should be printed in "portrait" orientation as opposed to "landscape"

Main Applications:

Production of high quality interior graphics requiring easy and clean removal from flat, painted wall surfaces (non-textured walls only), most types of wallpaper and wood paneling.

Recommended Application Surfaces:

Smooth, non-textured painted matte drywall
Smooth, non-textured gloss painted drywall
Other smooth, non-textured, non-porous surfaces (such as glass or metal)
Flat, smooth, finished wood surfaces such as doors and paneling.

Surfaces Not Recommended:

Textured Walls (speckled, orange peel, etc.)
Brick or concrete block, Unpainted Drywall, Outdoor walls
Direct application to vehicles
Any other surface that is rough, textured, uneven or porous.

Disclosure:

All product specifications and data are subject to change without notice. All recommended settings, properties and technical information are based upon tests that are believed to be reliable. Supplier disclaims any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product. Supplier disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify supplier's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products. The purchaser of this product has the sole responsibility for determining if the product described is a suitable fit for purchaser's application and intended use.

Liability for defective products shall not exceed the purchase price paid by purchaser for the product. If a product is found to be defective, as determined by supplier, the sole obligation of supplier and sole remedy for purchaser is replacement of the defective product without additional charge. No additional compensation for a defective product will be made. This document does not stand as a guarantee of performance or satisfaction.

Product names and markings noted herein may be trademarks of their respective owners.