VULCAN Information Packaging

Customer Supplied Film Laminated Wraps **SPECIFICATIONS**

Quantity Ordered	<u>Additional Wraps Needed</u>
25	20 pcs.
50	25 pcs.
100	40 pcs.
150	50 pcs.
200	56 pcs.
250	65 pcs. _–
300	75 pcs.
400	88 pcs.
500	100 pcs.
750	120 pcs.
1,000	130 pcs.
1,500	165 pcs.
2,500	250 pcs. L
5,000 and over	Add 7%

IMPORTANT!

Customer to supply wraps trimmed to Vulcan's template size. For trim sizes contact your Sales Rep.


> Questions? 1-800-633-4526

NOTE: If order amount is in-between quantity categories, go to next higher category. Example: 350 pc. order - add 88 pieces.

- Paper: 80# minimum, 100# preferred C1S Label
- Gloss Lamination: .5 mil gluable/stampable polyester (1.2 mil with adhesive)
- Matte Lamination: .5 mil gluable/stampable polypropylene (1.2 mil with adhesive)
- Miscellaneous:

Press sheets cannot have aqueous primer or coating prior to lamination. This will cause the lamination to detach from the binder leaving air bubbles.

Lamination to be applied to paper in a way that will cancel out the curling of the paper. Paper should be printed grain long (see diagram to right). Lamination must bleed past our cut lines to allow for excess trim on all four sides.



Sheets must arrive flat with no curling. Each stack must not exceed 30" tall. Sheets cannot cling together due to lamination, paper, static, etc. Sheets stacked over 30" create blocking/clinging due to weight factor. Each sheet is fed into automated equipment. Clinging causes multiple sheets to be inserted into the equipment causing those sheets to be spoiled.

Company Name:	Cianad:	Data
Company Name.	Signed:	Date.