
## **Machine Specifications - HD 6500**





Die Pin Retainer System

New for the HD 6500, this photo shows our ingenious die pin retainer system. Coupled with our Quick Change Slide Out Die System you will have the ultimate in versatility and productivity. Also shown is the adjustable punching margin control for the comb punch. Patent Numbers 5,771,768 & 6,047,623



What makes a Rhin-O-Tuff so Tuff?
Answer: **Heavy Duty Parts** like the gear box shown here.
Click on the gear box for a close up.

# 14" (356mm) HEAVY DUTY OPEN END PUNCH

#### **FEATURES**

Patented Anti-Jam Feature. Our New Overload
Detection Feature Triggers an
Auto-Reversing Function to Eliminate Jamming in the
Punch.

2-Bolt EZ Change Slide Out Die System

The HD 6500 Has More Than 20 Interchangeable Dies Available. 12 Hole Patterns are Standard. (Comes With Your Choice of a Standard Die)

Rated up to 40 Sheets or up to 80 Pages of 20 lb.or 80gsm. The Number of Sheets Depends on the Paper Weight and Punch Pattern Used. (15,000 to 18,000 SPH)

✓ 14" (356mm) Open Ended Punching, Allows for Wider Applications

90 Cycles Per Minute

Pre-set Paper Stop Guide for Easy Setup

All Punch Pins Easily Disengaged

Easy, "Paper to Pin", Sight Alignment, for Balanced Hole to Edge Margins on Odd-Sized Applications.

Use Foot Pedal, Versa Switch, or Palm Switch

1 Year Limited Warranty

Smooth, Quiet, Power on Demand Operation

Now Includes Commercial Chip Tray

All Metal Fabrication

#### THE ULTIMATE IN:

Quality Paper Punching and Book Binding Equipment at Affordable Prices

HD 6500 • MACHINE SPECIFICATIONS							
ELECTRICAL REQUIREMENTS			WEIGHT		DIMENSIONS		
VOLTS AC	AMPS	Hz	MACHINE	SHIPPING	HEIGHT	WIDTH	DEPTH
115	4	60	75 lbs	81.9 lbs	8"	17"	16¾"
230	2	50	34 Kg	37.15 Kg	203 mm	432 mm	426 mm
12 Standard Punch Die Patterns Available. All Other Patterns Available Upon Request.							

V

V

⊻

Now Includes Commercial Chip Tray.

### **Optional Features**

- Versa Switch (for paper activated punching)
- Commercial Die Rack [holds four (4) dies]