



Dual Hot roll Digital 44 Laminator

This newest addition to Ledco's Digital line is a 44" wide Hot Roll laminator. In addition to providing the same capabilities as the Heat Shoe Digital 42" and 60", the Dual Hot Roll Digital 44" offers the freedom to mount in one pass and to simultaneously mount and laminate.

With a top speed of 30 FPM and a sustainable laminating speed of 8-10 FPM the Dual hot roll Digital 44 performs faster than most competitive units. It is easy to thread and has a clear Plexiglas safety shield that provides the operator with visual access to the laminating process.

Standard features include a built-in release liner take-up and stand. The release liner allows for the application of any pressure-sensitive material that requires the removal of a protective liner. the wide range of temperatures available make this laminator perfect for almost any application up to 44" wide. The Dual Hot Roll Digital 44" will process thermal film, all pressure-sensitive materials, pre-mask, and mounting materials.

Specifications

Max. sheet size..... 44" wide

Speed.....0-30 FPM

Laminating pull Roller Diameter.....3-1/8"

Supply Roll Core Size.....3"

Take up Roll Core Size.....3"

Recommended Film.....Up to 10 MIL (hot/cold)

Max Laminating Thickness.....1/2"

Max Film roll Diameter.....12"

Dimensions.....62"W x 34"D x 60"H (26" H without stand)

Shipping Dimensions.....72"L x 39" H x 43"W

Weight/Shipping Weight.....550lbs/850lbs

Motor.....1/4 Horse D/C

Electrical (single phase).....208-240V single phase | 50-60 cycle 30
amps

Electrical Connector.....Nema 6-30p

Heater.....5500 watts