

# Pre-Masker 25" Pressure- Sensitive Tape Applicator



110 V -  
220 V – Optional

## **The solution to transfer taping and vinyl application headaches.**

The Pre-Masker automates the application of transfer tape, and other pressure-sensitive adhesive (PSA) tapes or films. It applies background vinyl or PSA films to sign blanks; it applies transfer-taped vinyl to any flat sign material, and will apply clear PSA overlaminates to finished signs or promotional materials. The Pre-Masker can be used to apply any type of pressure-sensitive film or tape to any substrate up to 7/16" thick. It can be used for mounting. The Pre-Masker is used in many settings, including sign shops, photo-finishing labs, reprographics shops and manufacturing plants.

## **Pre-Masker features include:**

- **A scrap rewind** with an adjustable clutch takes up the release liner found on many pressure-sensitive films.
- **Roller bearings**, alloy construction and high quality motors insure a long and trouble-free life for these machines.
- **The laminating roller opening** is adjustable in seconds and allows operators to work with different thickness materials.
- **A variable speed motor control** allows operators to apply different materials to different substrates.
- **Interchangeable rubber rollers** help keep maintenance costs down.
- **The feed tray** is non-ferrous, so magnetic materials may be applied.
- **The supply roll tension knobs** are important, because without some supply roll tension, most films

**Reduce labor costs.** Jobs such as applying vinyl to sign blanks or putting transfer tape on vinyl signage are very labor intensive, and prone to bubbles and wrinkles. When signage is ruined during the taping or application process, the cost of recutting, reweeding, and reapplying will usually take all the profit out of a job. Whether it's transfer tape, vinyl, sandblast or acid resist tape, premask, adhesive film, clear polyester, or other pressure-sensitive material, a Pre-Masker will put it down effortlessly with no bubbles or wrinkles.

**Save time/improve quality.** Using a Pre-Masker is much easier than doing the same work by hand. Fast and versatile, it requires little instruction for you to be up and running. Supply roll

- and tapes will wrinkle during application.
- **A reverse drive switch** makes it simple to back material out of the laminating rollers or correct material wrap-around.
  - **Manufactured in the U.S.A.** means quality, better service and faster parts availability.
  - **A bottom supply roll assembly**, an attached safety shield, and a feed tray with fixed left and right-side guides and one moveable guide, are standard.
  - **Removable power cord.**

tension is controlled with knobs. The laminating roller gap is adjusted with a single knob. Pre-Masker applicators are forgiving. They will apply most materials under a wide range of speeds and pressure or tension settings.

### Pre-Masker Tape Applicator:

PRODUCT	
Pre-Masker, 110v	Call
Pre-Masker, 220v	Call
Foot Switch	Call
Pre-Feed Slitter	Call

### Pre-Masker Specifications:

Max. lamination width	25"
Variable speed	0-10 fpm
Laminating roller diameter	1-1/4"
Supply roll core size	3"
Recommended film thickness	1 mil and up
Max. laminating thickness	7/16"
Max. film roll diameter	6"
Dimensions	33L 17H 18D
Shipping dimensions	36L 20H 20D
Weight/shipping weight	46/57
Motor	1/30 HP DC
Electrical	110V 220V option 3 amps 300 watts