

## **44" Wide Format Laminator (PL244WF)**



**This 44" wide laminator is specifically designed for wide format computer generated output. While priced below \$6,000 complete with welded steel stand, this machine is by no means a "lightweight". It can run film to 10 mils and laminate material to .275" thick. Warm up is less than 5 minutes. With optional liner take up assembly it is capable of utilizing pressure sensitive laminates as well. Due to superior heat replacement characteristics of our exclusive heated roll system, the PL-244wf is particularly suited to simultaneous mounting and laminating on heat activated adhesive foam board.**

**While providing the superior scratch and stretch free finish inherent with our heated roll technology the bond is so aggressive that any attempt to peel off laminated material will result in total destruction of foam board. This machine is specifically designed for wide format applications and will readily complement your ink jet printer. If you are in the market for a machine with more than a 3 foot wide capability that doesn't cost more than your shiny new 16 million color wide format printer, you would do yourself and the guy who writes the checks a very big favor by carefully examining the PL-244WF.**

## PL 244WF SPECS

|                         |  |
|-------------------------|--|
| Laminating Width        | 44   |
| Speed                   | Max Mechanical Speed: 6 fpm<br>1.5 CL 6 fpm @ 300 Degrees F<br>3.0 CL 3 fpm @250 Degrees F |
| Polypropylene Capable   | Yes  |
| Max Film Thickness      | 10.0 Mil   |
| Max Material Thickness  | .275   |
| Cooling Fans            | 3  |
| Warm Up Time            | Approx. 7 min  |
| Max Roll Dia. 1.5 mil   | w/o stand-1000' w/optional stand-3000'   |
| Stand                   | Optional w/3" Mandrels   |
| Gapable rolls           | Yes-Front Heat and Rear Pull   |
| Solid State Temp Cont.  | Yes-With Digital Readout   |
| Motor Speed Control     | Solid State/Variable   |
| Slitters                | Optional   |
| Heated Roll Watts       | 850 ea 1,700 combined  |
| Electrical Requirements | 240 Volt 60Hz 16Amps   |
| Dimensions              | 49Wx20Dx16H-w/o stand 40H-w/ stand   |
| Weight                  | Net 120 lbs Shipping 170 lbs<br>(LAMINATOR) + 85 (STAND)                                   |
| Shipping Dimensions     | 56"Wx21"Dx19H  |