

The new SH-620HD provides the perfect solution for economical mid-volume high quality single side lamination of book covers, brochures, magazine covers, and more.

- ▶ **Laminator for Digital Printing**
- ▶ **Operated by Pneumatic System**
- ▶ **Semi-automatic feeding**
- ▶ **Automatic laminating and separating**

Features:

- ◆ Maximum 8.0m/min Laminating speed provides high productivity.
- ◆ Large Chrome plated heat roller increases thermal capacity
- ◆ Infrared temperature sensor and CPU control system enables reliable control
- ◆ Pneumatic System provides accurate Overlapping, nip pressure and bursting.
- ◆ Adjustable decurling device with cooling blowers ensures flat sheets
- ◆ Both sides opened film shaft eases film loading.
- ◆ In-line film slit and perforator allows film for any sheet size
- ◆ Job sheet counter tracks usage



Specifications

Model	SH-620HD
Laminating Speed	Up to 8.0 m/min
Laminating Width	620mm
Max Nip Opening	20 mm
Max Working Temperature	150°C
Warm Up Time	About 15 min
Laminating Films	BOPP
Type of paper	120—350 gsm
Film Core size	76mm
Control System	Infrared temperature sensor and 8-bit CPU control
Heating System	Hot Roller Internal Infrared Heater
Cooling system	5 High speed cooling fans
Roller lift-up system	Pneumatic
Pneumatic Working Pressure	0.6 MPa
Power Requirements	AC220V-240V, 50/60Hz
Power Consumption	1700W, 8A
Dimensions(LXWXH)	1420 (L) x 963 (W) x 1470(H) mm (with stand)
Machine weight	210 kgs



NSC INTERNATIONAL
7090 CENTRAL AVE, HOT SPRINGS, AR, 71913
PHONE (727) 857-1100 / FAX (727) 857-1112
www.binding.com