## **SUPERSHRINK®**

## Polyolefin Shrink Film

SuperShrink® Polyolefin films offer superior optical properties, package durability and seam strength. New cross-linked SuperShrink® SSP55-I and SSP-PLUS (soft shrink) are competitive next-generation films designed for strength and improved machinability on both manual and automatic equipment.



Available as:

Center Fold (CF)
Single Wound (SW)



Pre-perforated patterns available upon request.



SSPX-I	MULTI-LAYER POLYOLEFIN
SUBSTRATE	SSPXI SUPERSHINK POLYOLEFIN ROLL FILM
SIZES	5-44 inches
GAUGES	45, 60, 75, 100, 125
SHRINKAGE	265° - 65% MD, 65% TD (varies with gauge/size)
COLOR	Crystal Clear or Print up to 8 colors
SHIPPING	In Stock Film Ships in Two Business Days
USE	High-speed, Excellent clarity, Short dwell time
CCD DLUC	CROSS LINKED SOFT SURINK BOLVOLESIN
SSP-PLUS	CROSS LINKED SOFT SHRINK POLYOLEFIN
SUBSTRATE	SSP-PLUS SUPERSHINK POLYOLEFIN ROLL FILM
SIZES	5-44 inches
GAUGES	45, 50
SHRINKAGE	250° - 75% MD, 75% TD (varies with gauge/size)
COLOR	Crystal Clear or Print up to 8 colors
SHIPPING	In Stock Film Ships in Two Business Days
USE	Strong, Durable, Low Temp, High Speed
UJL	Strong, Darable, Low Temp, High Speed
SSPY	HIGH SPEED POLYOLEFIN
SUBSTRATE	SSPY SUPERSHRINK POLYOLEFIN ROLL FILM
SIZES	4-78 inches
GAUGES	45, 60, 75, 100, 150
SHRINKAGE	250° - 70% MD, 70% TD (varies with gauge/size)
COLOR	Crystal Clear, Tine, Opaque or Print up to 8 colors
	,
SHIPPING	In Charle Films China in Two Descinas Davis
	In Stock Film Ships in Two Business Days
USE	In Stock Film Ships in Two Business Days Low Temp, Good Hotslip, High Speed
	Low Temp, Good Hotslip, High Speed
	,
USE	Low Temp, Good Hotslip, High Speed
USE SSP55-I	Low Temp, Good Hotslip, High Speed  ECONOMY CROSSLINKED POLYOLEFIN
SSP55-I SUBSTRATE	Low Temp, Good Hotslip, High Speed  ECONOMY CROSSLINKED POLYOLEFIN  SSP55-I ECONOMY POLYOLEFIN ROLL FILM 6-80 inches
SSP55-I SUBSTRATE SIZES GAUGES	Low Temp, Good Hotslip, High Speed  ECONOMY CROSSLINKED POLYOLEFIN  SSP55-I ECONOMY POLYOLEFIN ROLL FILM 6-80 inches 60, 75
SSP55-I SUBSTRATE SIZES GAUGES SHRINKAGE	Low Temp, Good Hotslip, High Speed  ECONOMY CROSSLINKED POLYOLEFIN  SSP55-I ECONOMY POLYOLEFIN ROLL FILM 6-80 inches 60, 75 265° - 80% MD, 80% TD (varies with gauge/size)
SSP55-I SUBSTRATE SIZES GAUGES	Low Temp, Good Hotslip, High Speed  ECONOMY CROSSLINKED POLYOLEFIN  SSP55-I ECONOMY POLYOLEFIN ROLL FILM 6-80 inches 60, 75

Economical, Strong Seal, Low Temp

